

Vintage's Canadian made Northern Solid Sawn™ is the next generation of high performing structured hardwood floors. Backed by the best stability warranty in the business and trend hitting colors, textures and widths will provide you with a lifetime of satisfaction.



Maple, Pegasus

SMOOTH				WIRE BRUSHED		ETCHED	
MAPLE		RED OAK	WHITE OAK	BLACK WALNUT	RED OAK	WHITE OAK	MAPLE
NATURAL	NEBULA	NATURAL*	NATURAL*	NATURAL	NATURAL*	ATLANTIS*	ICELAND
OXFORD	MOROCCO	KAHLUA*	NAUTILUS*	MEDIEVAL	KAHLUA*	PHARAOH*	MALDIVES
PEGASUS	REMBRANDT	MOCHA*	ORACLE*		BERKSHIRE*	ORION*	SAMOA
WINDSOR	GODIVA	BERKSHIRE*	ATHENA*		CHARIOT*	ZEUS*	BORNEO
ARIES	TABOO	CHARIOT*	APOLLO*		COCOA*	GOTHAM*	GALAPAGOS
		COCOA*	GABON*		TITAN*	BAROQUE*	TAHITI
		GRYPHON*	BUCKINGHAM*		GRYPHON*	BUCKINGHAM*	<b>BLACK WALNUT</b>
		PEWTER*	BAROQUE*		PEWTER*		NATURAL
			GOTHAM*				

\*Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.

# NORTHERN SOLID SAWN™ SPECIFICATIONS

**Product Type:**

Structured Northern Solid Sawn™

**Product Species:**

Black walnut, Maple, Red Oak, White Oak

**Product Grade & Widths:**

Availability of widths will vary by grade and color. Refer to availability chart for more information.

Select-V: 3 1/4" (84mm), 4 3/8" (112 mm), 5" (127mm)

Character: 5" (127 mm)

Herringbone: Red Oak Estate 3 1/4" (84 mm) x 14.68" (372 mm)

White Oak Select-V: 3 1/4" (84 mm) x 14.68" (372 mm),

Character 5" (127 mm) x 30" (762 mm)

**Product Lengths:**

Estate & Select-V: 15" - 70" Average 33" (381 mm - 1750 mm Ave. 838 mm) Character: 20" - 83" Average 42" (511 mm - 2107 mm Ave. 1066 mm)

**Product Gloss:**

White Oak Select-V: Pearl  
 Red Oak Estate: Semi-gloss & Pearl  
 Black Walnut, Maple Estate & Select-V: Pearl  
 Maple, White Oak Character: Pearl  
 Wire Brushed Red Oak, White Oak Character: UV Urethane Oil  
 Etched Maple Estate & Walnut Select-V: UV Urethane Oil

**Product Grade:**

Estate - Best grade available  
 Select-V: Color variation and naturally occurring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade.  
 Character: Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation in knot size) checks and splits. Some voids are allowed.

**Product Thickness:**

3/4" (19 mm) 3 ply structured

**Face Lamella:**

4mm

**Core Layer:**

13 mm SPF Qtr. Sawn

**Back Layer**

2 mm Hardwood veneer

**Installation Method:**

Nail, Glue or Float

Herringbone: Glue

**Sanding:**

Can be professionally sanded 3-4 times

**Radiant Heat:**

Yes for all species, see Radiant Heat Warranty

**Structural Warranty:**

Lifetime

**Lifetime Stability Warranty:**

Relative humidity must be maintained between 25-70%

**Residential Warranty:**

25-Year for Pearl & Semi-gloss, 10-Year for UV Urethane Oil

**Commercial Warranty:**

3-Year for Pearl & Semi-gloss, 1-Year for UV Urethane Oil

