

HAND SCRAPED SPECIFICATIONS

Product Type:

3/4" (19mm) Solid Sawn® 3 layer Structured Tongue and groove with bevel on 4 sides

Product Species:

White Oak Plain Sawn

Product Textures & Gloss:

Hand Scraped: Pearl

Product Lengths:

5" & 7" Character: 16" - 84" Average 44" (406 mm - 2134 mm Ave 1118 mm) 10" Character: 24" - 114" Average 58" (610 mm - 2896 mm Ave 1476 mm)

Product Grade & Width:

White Oak Plain Sawn: Character 5", 7", 10" See availabilty chart for more information

Character: Unlimited color variation and naturally occuring charactertistics, sound filled knots (no limitation of knot size), sheeks and splits. Some voids are allowed.

checks and splits. Some voids are allowed.

Face lamella:

5/32" (4 mm) sawn solid hardwood

Core layer:

3/8" (10 mm) solid finger core

Back layer:

3/16" (5 mm) solid finger core

Approved over Radiant heat

Radiant Heat:

Installation Method:

Nail, glue or float at, above or below grade

Subfloor:

3/4"
19mm
Thickness

4 mm Sawn wear lamella
Solid lumber finger core
Hardwood back
Superior lengths: 16"- 114"
(406 mm - 2896 mm)

Relative Humidity Chart



Floated installation relative humidity warranty is 30 - 60%

Installation methods



Consult Vintage's Radiant Heat compliance information at vintageflooring.com











LIFETIME stability warranty LIFETIME structural warranty

35 YEARS residential wear warranty

3 YEARS commercial wear warranty

24/0

