

WHITE OAK RIFT & QTR. SAWN SPECIFICATIONS

Product Type:

Product Species:

Product Textures & Gloss:

Product Lengths:

Product Grade & Width:

Face lamella:

Core layer:

Back layer:

Sanding: Radiant Heat:

Installation Method:

Subfloor:

3/4" (19mm) Northern Solid Sawn® 3 layer Structured Tongue and groove with micro-v bevel on 4 sides

White Oak

Wire Brushed: White Oak: UVF

Select-V: 15" - 70" Average 33" (373 mm - 1778 mm Ave 838 mm)

White Oak Rift & Qtr. Sawn: Select-V 5", 6 1/2"

Select-V: Color variation and naturally occuring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade.

Rift & Quarter Sawn wood is cut at a specific angle to increase stability and minimize warping. Rift Sawn wood has a linear look and the Quarter Sawn wood has an amazing ribbon-like effect and some flecking. These cuts of wood are combined since they compliment each other to create a beautiful, stable floor.

5/32" (4 mm) sawn hardwood

17/32" (13 mm) SPF Qtr. Sawn

1/16" (2 mm) wood veneer

Can be professionally sanded 3-4 times

Approved over Radiant heat

Nail, glue or float at, above or below grade

Wood or concrete



Relative Humidity Chart







LIFETIME stability warranty

LIFETIME structural warranty

35 YEARS residential wear warranty

3 YEARS commercial wear warranty

