


A uniquely beautiful and stable floor reminiscent of Black Walnut is created when White Oak goes through a fuming process that brings out the natural tannins of the wood. This process allows the color to penetrate the lamella so that scratches and dents will blend in more. Certain Vintage products such as Excalibur and Spartacus are then stained to produce amazing tones of gray and caramel.




Hand Scraped White Oak, Old Oak

**SMOOTH
WHITE OAK**



**HAND SCRAPED
WHITE OAK**




**WIRE BRUSHED
WHITE OAK**



SOLID SAWN® FUMED WHITE OAK SPECIFICATIONS




Product Type:	3/4" (19 mm) Structured Solid Sawn®
Product Species:	White Oak
Product Width:	5" (127 mm), 7" (177 mm)
Product Lengths:	Character: 18" – 84" Average 42"
Product Gloss:	Smooth: Black Oak, Old Oak-Pearl or UV Urethane Oil Excalibur, Greystoke-UV Urethane Oil Wire Brushed: Spartacus-UV Urethane Oil Hand Scraped: Old Oak-Pearl or UV Urethane Oil Greystoke-UV Urethane Oil
Product Grade:	Character (Fumed)
Product Construction:	3 Ply Structured
Face Lamella:	4 mm Solid Species
Core Layer:	10 mm Solid Finger Core - Same or alike species
Back Layer:	5 mm Solid Finger Core - Same or alike species
Installation:	Nail, Glue or Float.
Coating Type:	Pearl or UV Urethane Oil
Structural Warranty:	Lifetime Structural Warranty
Lifetime Stability Warranty:	Relative humidity must be maintained between 25-70%
Residential Warranty:	25-Year Wear Warranty for Pearl 10-Year Wear Warranty for UV Urethane Oil
Commercial Warranty:	3-Year Wear Warranty for Pearl 1-Year Wear Warranty for UV Urethane Oil



Consult Vintage's radiant heat compliance information available at www.vintageflooring.com

Relative Humidity Chart



3/4" (19 mm) Structured

