



NORTHERN SOLID SAWN®

(3 LAYER STRUCTURED WOOD CORE)

Real hardwood boards with SPF quarter sawn core and wood backing.

VALIDATED ECO-DECLARATION

PRODUCT SPECIFICATIONS

Reference

3 layer structured wood core (Northern Solid Sawn)

Final manufacturing location

Toronto, ON M8Z 1K8 or Saint-Georges, QC G5Y 8J5 CANADA

Components

SPF core, hardwood lamella, veneer, adhesives and finishes.

ATTRIBUTES

Recycled Content

Pre-consumer: 0% Post-consumer: 0%

Sourcing of raw materials

The source of extraction and/or location of raw materials has been documented for 89.2% of final product weight.

Certified Wood	PEFC 54327
Rapidly renewable materials	-
Biobased materials	-

ENVIRONMENTAL IMPACTS

Life Cycle Assessment
Reference service life -

Product's carbon footprint

Environmental Product Declaration

ISO 14025:2006

INGREDIENTS AND EMISSIONS

Declaration of chemical 1,000 ppm

Type of declaration HPD® version 2.2 Health Product Declaration® September 2021 - September 2024

Emission tests Complying with the CDPH

VOCs CDPH test results ≤ 0.5 mg/m³

Formaldehyde CDPH test results ≤ 9.0 ug/m³

Others

TECHNICAL PERFORMANCES

©Copyright 2016 Vertima inc.

Performance tests

Relevant performances tests list. Fire reaction available on request.

MANUFACTURER'S ENVIRONMENTAL MANAGEMENT

ISO 14001 Certification

Extended Producer Responsibility (Take Back Program)

Corporate Sustainability Report (CSR: GRI, ISO 26000, BNQ 21000 or others)

CERTIFICATIONS AND CONFORMITIES







As an innovative leader in the prefinished hardwood flooring market, Vintage Hardwood Flooring has built a reputation of exceptional quality and service both across Canada and in the United States.

MasterFormat®: **09 64 00** Validated Eco-Declaration: **VED16-1071-04**

Original issue date: **07/2016**Period of validity: **04/2021** to **04/2022**



3 LAYER STRUCTURED WOOD CORE (NORTHERN SOLID SAWN)





Characteristics

- · Boards with uniform thicknesses and widths
- · Micro-V joint on all four sides of the board
- Radiant heat approved for most species

ATTRIBUTES

RECYCLED CONTENT

Final product	Weight ratio	Pre-consumer	Post-consumer
3 layer structured wood core (Northern Solid Sawn)	100%	0%	0%

Validated Eco-Declaration - Recycled Content

Methodology: on-site audit, supply chain evaluation, analysis and validation of the recycled content data according to the weight ratio of each of the components used in manufacturing the final product.

Vertima's procedure: VERT-032008-01, Second Edition.

SOURCING OF RAW MATERIALS

Weight ratio	Final manufacturing location
100%	Toronto, ON M8Z 1K8 CANADA or Saint-Georges, QC G5Y 8J5 CANADA

Validated Eco-Declaration - Sourcing of raw materials

Methodology: on-site audit, supply chain evaluation, analysis and validation of the sourcing of raw materials data according to the weight ratio of each of the components used in manufacturing the final product.

Vertima's procedure: VERT-032008-02, Second Edition

Component	Weight ratio	Extraction location	Transportation
SPF core	63.2% - 65.1%	Canada and United States	Road and boat
Hardwood lamella	26.0% - 26.1%	Canada and United States	Road and boat
Veneer	7.0% - 8.8%	Various locations	Road and boat
Adhesives	<1.0%	N/A	N/A
Finishes	<1.0%	N/A	N/A

The source of extraction and/or location of raw materials has been documented for 98.0% of final product weight.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and/or omissions relative to the collection, compilation and/or interpretation of data.

Copyright® 2016 by Vertima Inc.







ATTRIBUTES (CONTINUED)

SOURCING OF RAW MATERIALS (CONTINUED)



1. WOOD HARVEST LOCATION - SPF core & Hardwood lamella (Details available upon request)

Canada: Quebec, New Brunswick, Ontario.

United States: Arkansas, Connecticut, Delaware, Illinois, Indiana, Iowa, Kentucky, Maine, Maryland, Massachusetts, Michigan, Missouri, New Hampshire, New Jersey, New York, North Carolina, Ohio, Pennsylvania, Rhode Island, South Carolina, Tennessee, Vermont, Virginia, West Virginia, Wisconsin.

2. VENEER HARVEST LOCATION (Details available upon request)









ATTRIBUTES (CONTINUED)

CERTIFIED WOOD

When specified, PEFC certified 3 layer structured wood core (Northern Solid Sawn) could be available. (Contact Vintage for availability)



Certification agency			Product covered
Bureau de normalisation du Québec (BNQ)			Wooden floor
Certificate site	Certification number	Traceability method	Period of validity
BOA-FRANC INC. St-Georges, QC CANADA	54327	Credit system	2017/12/21 to 2022/12/20

Validated Eco-Declaration - Certified Wood

Methodology: on-site audit, supply chain evaluation and validation of certified wood documents confirming the type of certification. Vertima's procedure: VERT-032008-03, Second Edition.

TECHNICAL PERFORMANCES

PERFORMANCE TESTS

Contact manufacturer for more details.

WARRANTY

See product detailed description.


MANUFACTURER'S ENVIRONMENTAL MANAGEMENT PROGRAM

RESPONSIBLE RAW MATERIALS PROCUREMENT REPORT

Report name	Date
Controlled Wood Risk Evaluation	Updated annually



Validated Eco-Declaration - Supply Chain Management Report Methodology: validation of documents attesting the supply chain management report. Vertima's procedure: VERT-032009-04, First Edition.





3 LAYER STRUCTURED WOOD CORE (NORTHERN SOLID SAWN)



INGREDIENTS AND EMISSIONS

DECLARATION OF CHEMICAL INGREDIENTS



Type of declaration: Health Product Declaration® (HPD®) version 2.2

Period of validity: September 2021 - September 2024 **HPD name:** 3 layer structured wood core – Toronto

Summary of product contents and results from screening individual chemical substances against HPD Priority Lists¹ and the GreenScreen for Safer Chemicals^{®,2}.

HPDC repository URL:

https://hpdrepository.hpd-collaborative.org/repository/HPDThumbnails/D406664046D985612494F5568992BF57.jpg

The presented results are specific to 3 layer wood core prefinished at Toronto plant. For more details about the HPD® related to 3 layer wood core prefinished at St-Georges plant and entitled "3 layer wood core - St-Georges", please consult the HPD Public repository.

The Health Product Declaration® and logo is owned by the Health Product Declaration® Collaborative and is used with permission.

Declaration: ■ Prepared by Vertima inc., third party approved by HPDC

Ingredients inventory threshold: 1,000 ppm Full disclosure of intentional ingredients: Yes Full disclosure of known hazards: Yes

Hazard(s) associated with the product ingredients: (Not associated with actual use of finished product)

This HPD Standard describes a declaration of product content and direct health hazards associated with exposure to its individual contents. The Declaration is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes

Highest concern GreenScreen® Benchmark: Benchmark 13

PBT (Persistent, Bioaccumulative, Toxic)
Cancer
Gene mutation

□ Development

Neurotoxicity Mammal

Respiratory

Land toxicity Aquatic toxicity Ozone depletion Multiple Unknown

Physical hazard

☐ Global warming

Reproductive Endocrine Skin or eye

Refer to Annex D of HPD® Open Standard Version 2.1, May 2017: http://www.hpd-collaborative.org 2GreenScreen for Safer Chemicals® method: http://www.greenscreenchemicals.org/ GreenScreen (GS) Benchmark scores of chemical ingredients: Benchmark 1 (Avoid, chemical of high concern), Benchmark 2 (Use but search for safer substitutes), Benchmark 3 (Use but still opportunity for improvement), Benchmark 4 (Prefer, safer chemical).

TABLE OF INGREDIENTS

Component	Role	Weight ratio	CAS ¹	GreenScreen®,2	Other applicable score
SPF core	Main element	62.9% - 67.5%	-	-	-
Hardwood lamella	Main element	23.7% - 26.7%	-	-	-
Veneer	Main element	7.0 - 9.2%	-	-	-
Finishes	Finishes	<1.0%	14807-96-6, 14808-60-7, Undisclosed	BM-1	LT-1, LT-P1 and LT-UNK scores also present
Adhesives	Assembly	<1.0%	1333-86-4, Undisclosed	BM-1	LT-P1, LT-UNK, BM-4, BM-3, BM-3dg and LT-1 scores also present
Stain	Color the wood	< 0.5%	1333-86-4	BM-1	LT-1, LT-P1 and LT-UNK scores also present
Wood Filler	Wood Filler	< 0.3%	1317-65-3	BM-3dg	LT-UNK score also present

Only the CAS numbers with the score of highest concern are listed. The complete list of substances can be found in the HPD®

²GS List Translator (LT) scores of chemical ingredients: LT-1, likely GS Benchmark 1; LT-P1, possible GS Benchmark 1; LT-U or LT-UNK, present on GS Specified Lists but there is insufficient information to classify the hazards as LT-1 or LT-P1 (does not mean the chemical is safe). Validated Eco-Declaration – Declaration of chemical ingredients

Methodology: validation of the documentation confirming the methodology and reporting of chemical ingredients.

Vertima's procedure: VERT-032009-01, Second Edition.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and/or omissions relative to the collection, compilation and/or interpretation of data Copyright® 2016 by Vertima Inc.



3 LAYER STRUCTURED WOOD CORE (NORTHERN SOLID SAWN)



INGREDIENTS AND EMISSIONS (CONTINUED)

EMISSION TESTS

Reference Standard



California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017

(Emission testing method for CA Specification 01350) **Certificate number:** 210305-04 (Cashmere, SG & Pearl)

Issue Date: March 5, 2021

Final maunfacturing location: St-Georges, QC / Toronto, ON

Analytical Lab: Berkeley Analytical (select the right finish to access the appropriate document)



Acceptance Criteria and Results Demonstrating Compliance of Product Sample to Referenced Standard:

Exposure Scenario ¹	Individual VOCs of Concern ²		Formal	dehyde³	TVOC⁴
	Criterion	Compliant	Criterion	Compliant	Range
School Classroom	≤½ Chronic REL	Yes	≤9.0 µg/m³	Yes	≤0.5 mg/m³
Private Office	≤½ Chronic REL	Yes	≤9.0 µg/m³	Yes	≤0.5 mg/m³

Product Coverage⁵: Not applicable

Source: Berkeley Analytical - VOC Emission Test Certificate

Reference Standard



California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017

(Emission testing method for CA Specification 01350)

Certificate number: 210518-02 (DuraMatt, UVF & Oiled)

Issue Date: May 18, 2021

Final maunfacturing location: St-Georges, QC / Toronto, ON

Analytical Lab: Berkeley Analytical (select the right finish to access the appropriate document)



Acceptance Criteria and Results Demonstrating Compliance of Product Sample to Referenced Standard:

Exposure Scenario ¹	Individual VOCs of Concern ²		Formal	dehyde³	TVOC⁴
	Criterion	Compliant	Criterion	Compliant	Range
School Classroom	≤½ Chronic REL	Yes	≤9.0 µg/m³	Yes	≤0.5 mg/m³
Private Office	≤½ Chronic REL	Yes	≤9.0 µg/m³	Yes	≤0.5 mg/m³

Product Coverage⁵: Not applicable

Source: Berkeley Analytical - VOC Emission Test Certificate

Exposure scenarios & product quantities for classroom & office are defined in Tables 4-2 - 4-5 (CDPH Std. Mtd. V1.1-2010).


²Maximum allowable concentrations of individual target VOCs are specified in Table 4-1 (ibid).

³Maximum allowable formaldehyde concentration is ≤9 μg/m³, effective Jan 1, 2012; previous limit was ≤16.5 μg/m³ (ibid).

 4 Informative only; predicted TVOC Range in three categories, i.e., ≤ 0.5 mg/m 3 , > 0.5 - 4.9 mg/m 3 , and ≥ 5.0 mg/m 3 .

⁵Informative and applicable only to tests of wet-applied products; grams of sample applied per square meter of substrate.

Validated Eco-Declaration—Emissions testing Methodology: validation of documents certifying the test results. Vertima's procedure: VERT-032009-02, Second Edition.









PRODUCT CONTRIBUTION SUMMARY

LEED® v4 requirements for Building Design + Construction (BD+C)

New Construction and Major Renovation, Core and Shell, School, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

LEED® v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

MATERIALS AND RESOURCES		PF	RODUCT CONTRIBUTIONS
	Building Product Disclosure and Optimization		ATTRIBUTES
MR	— Sourcing of Raw Materials Option 2: Leadership extraction practices (1 point) See Pilot-Credits MRpc102: Legal Wood	Contribute (pilot-credits)	PEFC Certification (when specified)
	Building Product Disclosure and Optimization — Material Ingredients		INGREDIENTS AND EMISSIONS
MR	Option 1: Material ingredients reporting (1 point) The 3 layer structured wood core (Northern Solid Sawn) contributes to this credit due to the availability of Health Product Declarations® and is valued as 1 whole product out of the 20 needed for the purposes of credit achievement calculation.	Contribute	HPD® version 2.2 Health Product Declaration®
INDOOF	R ENVIRONMENTAL QUALITY	PF	RODUCT CONTRIBUTIONS
	Low-Emitting Materials		INGREDIENTS AND EMISSIONS
EQ	Option 1: Product category calculation (1-3 points) Number of points is dependent on the LEED rating system and the number of compliant categories. For the flooring category 100% of flooring must meet the requirements.	Contribute	The 3 layer structured wood core (Northern Solid Sawn) has been tested according with the standard method of the California Department of Public Health (CDPH).

LEED® v4 requirements for homes

Applies to single family homes, multi-family (one to three stories), or multi-family (four to six stories). Includes homes and multifamily low-rise and multi-family mid-rise.

MATERIALS AND RESOURCES		PRODUCT CONTRIBUTIONS	
MR Prerequisite	Certified Tropical Wood	-	ATTRIBUTES To meet the prerequisite, don't select tropical species of Vintage.
MR	Environmentally Preferable Products Maximum of 4 points depending on both options in the context of each project. Option 2: Environmentally Preferable Products Wood products must be FSC®-Certified, or USGBC-approved equivalent. See Pilot-Credits MRpc102: Legal Wood The 3 layer structured wood core (Northern Solid Sawn) meets at least 1 criterion for this option since the product is PEFC Certified when specified.	Contribute (pilot-credits)	PEFC Certification (when specified)
INDOOR ENVIRONMENTAL QUALITY		PF	RODUCT CONTRIBUTIONS

INGREDIENTS AND EMISSIONS

Low-Emitting Products (0.5-3 points)

E₀

At least 90% of all materials in each category must meet credit requirements.

Contribute

The 3 layer structured wood core (Northern Solid Sawn) has been tested according with the standard method of the California Department of Public Health (CDPH).

It is important to consider that the total amount of possible points reflects the number of achievable points in each credit category. The product itself cannot achieve this score, as defined above, but is considered as a beneficial element in order to obtain LEED® credits.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and/or omissions relative to the collection, compilation and/or interpretation of data Copyright® 2016 by Vertima Inc.

