

HERRINGBONE SPECIFICATIONS

HERRINGBONE SPECIFICATIONS				
Product Type:	3/4" (19mm) Northern Solid Sawn® Tongue and groove with bevel o	^a 3 layer Structured n 4 sides	NORTHERN 💽	— 4 mm Sawn wear Iamella
Product Species:	White Oak Plain Sawn		alles and	Qtr. Sawn finger core
Product Textures & Gloss:	Smooth: Pearl & UVF Wire Brushed: UVF Sculpted: UVF		3/4" 19mm Thickness	- Wood back Superior lengths : 15*- 82* (381 mm - 2086 mm)
Product Lengths:	Select-V 14.68" (373mm) Character 30" (762mm)		Relative Humidit	y Chart
Product Grade	Select-V 3 1/4" x 14.68", Character	5" x 30"		
& Width:	Select-V: Color variation and nai 1/4" sound filled knots, some voids checks and knots on bevel are n	25-809 Floated installation relo warranty is 30	itive humidity	
	Character: Unlimited color variat charactertistics, sound filled knot checks and splits. Some voids ar	s (no limitation of knot size),		ethods
Face lamella:	5/32″ (4 mm) sawn hardwood		YES - ABOVE GROUND I	EVEL
Core layer:	17/32" (13 mm) SPF Qtr. Sawn		YES - GROUND LEVE	1
Back layer:	1/16" (2 mm) wood veneer YES - BELOW GROUND LEVEL			
Sanding:	Can be professionally sanded 3-	4 times	RADIANT HEA Consult Vintag	je's
Radiant Heat:	Approved over Radiant heat		Radiant Heat com information vintageflooring:	at
Installation Method:	Glue down			
Subfloor:	Plywood or concrete			FLOAT
				haracter Nautilus UVF
	LIFETIME stability warranty	LIFETIME structural warranty	35 YEARS residential wear warranty	3 YEARS commercial wear warranty 23/01
409 Evans Ave. To Tel: (416) 252-0962 Toll Free: 1-877-256	ronto, Ontario M8Z 1K8 2 3-0231		vin	tageflooring.com 👎 🞯 🗭 🎰