

CHEVRON SPECIFICATIONS

Product Type:

3/4" (19mm) Northern Solid Sawn® 3 layer Structured
Tongue and groove with bevel on 4 sides

Product Species:

White Oak Plain Sawn

Product Textures & Gloss:

Smooth: Pearl & UVF
Brushed: UVF

Product Lengths:

Character 24.4" (620mm)

Product Grade & Width:

Character 5" x 24.4"

Character: Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation of knot size), checks and splits. Some voids are allowed.



Relative Humidity Chart



Face lamella:

4 mm sawn hardwood

Core layer:

13 mm SPF finger core, predominantly Qtr. Sawn

Back layer:

2 mm wood veneer

Sanding:

Can be professionally sanded 3-4 times

Radiant Heat:

Approved over Radiant heat

Installation Method:

Glue down

Subfloor:


Plywood or concrete

Installation methods




Consult Vintage's Radiant Heat compliance information at vintageflooring.com


PATTERNS




CHEVRON




SPEARHEAD



BROOKLYN BRIDGE



LEAF LINE



BOARDWALK



Brushed White Oak Character Atlantis UVF

LIFETIME

stability warranty

LIFETIME

structural warranty

35 YEARS

residential wear warranty

3 YEARS

commercial wear warranty