

U-LOC[®] is Vintage's Do-it-yourself friendly product. It is unique as it is a structured floating floor with an easy to install locking system making installation quick and easy. U-LOC[®] comes in Select-V Grade in 4 1/4" width and lengths ranging from 13" (350 mm) to 46" (1177mm). Available in Hickory, Maple and Red Oak species, U-LOC[®] flooring is a great addition to any room in your home or condominium.




Red Oak, Natural

| SMOOTH | | |
|---------|-----------|---------|
| HICKORY | MAPLE | RED OAK |
| NILE | OXFORD | NATURAL |
| MOOREA | PEGASUS | MOCHA |
| | WINDSOR | GRYPHON |
| | REMBRANDT | COCOA |

U-LOC® SPECIFICATIONS



| | |
|-------------------------------------|---|
| Product Type: | U-LOC® Hardwood Flooring |
| Product Species: | Red Oak, Maple & Hickory |
| Product Width: | 4 1/4" |
| Product Lengths: | 13.77" (350mm), 17.32" (440mm), 23.07" (586mm), 28.8" (732mm), 32.36" (822mm), 46.14" (1172mm) |
| Product Gloss: | Pearl |
| Product Grade: | Color variation and naturally occurring characteristics |
| Product Construction: | Locking hardwood flooring, 4 sided micro bevel |
| Product Thickness: | 11 mm |
| Face Thickness: | 2.0mm sawn face lamella |
| Core Layer: | HDF (High Density Fiberboard) |
| Back Layer: | Wood |
| Installation Method: | Floating Application Only |
| Underpad: | Vintage's Premium underpad 2mm |
| New Leed Credits: | MRC7 Certified Wood - FSC® is available by S/O MRC5 Regional Materials - This may apply depending on site location and mode of transportation |
| Compliance: | CARB 93120 Compliant Lacey Act Compliant |
| Structural Warranty: | Lifetime |
| Lifetime Stability Warranty: | Relative humidity must be maintained between 40% - 60% |
| Residential Warranty: | 25-Year Wear Warranty |
| Commercial Warranty: | 3-Year Limited Warranty |



Not all species are warranted over radiant heat. Consult your dealer for further information.



Float

Install over plywood or concrete with Vintage's Black Gold underpad.

