

## PIONEERED® SOLID SPECIFICATIONS

**Product Type:** 

3/4" (19mm) solid

Tongue and groove with micro-v bevel on 4 sides

**Product Species:** 

Hickory, Maple, Oak, Red Oak

**Product Textures** & Gloss:

Smooth: Hickory, Maple, Red Oak: Pearl

**Product Lengths:** 

**Product Grade** & Width:

Depending on width

Hickory: Character 2 1/4", 3 1/4", 4 1/4" Maple: Select-V 2 1/4", 3 1/4", 4 1/4"

Select-V: Color variation and naturally occuring characteristics, 1/4" sound filled knots, some voids are allowed. Splits,

Character: Unlimited color variation and naturally occuring charactertistics, sound filled knots (no limitation of knot size),

Can be professionally sanded 3-4 times

**Radiant Heat:** Not approved over Radiant heat

**Installation Method:** 

Sanding:

Subfloor:

Wire Brushed: Red Oak: UVF

Sculpted: UVF Blade: UVF

Select-V: 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm)

Character: 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm)

Oak: Character 4 1/4"

Red Oak: Select-V 21/4", 31/4", 41/4"

Character 4 1/4"

checks and knots on bevel are not part of this grade.

checks and splits. Some voids are allowed.

Plank: Nail down on plywood at or above ground level

Plywood



LIFETIME stability warranty

LIFETIME structural warranty

35 YEARS residential wear warranty

PIONEERED®

Relative Humidity Chart

Installation methods

ABOVE GROUND LEVEL

GROUND LEVEL

BELOW GROUND LEVE (NO INSTALLATION)

YES

YES

NO

3/4" 19mm

> 3 YEARS commercial wear warranty

Superior lengths

Small micro-v bevel

