

CHEVRON SPECIFICATIONS

Product Type:

3/4" (19mm) Northern Solid Sawn® 3 layer Structured Tongue and groove with bevel on 4 sides

Product Species:

White Oak Plain Sawn

Product Textures & Gloss:

Smooth: Pearl & UVF
Brushed: UVF

Product Lengths:

Character 24.4" (620mm)

Product Grade & Width:

Character: Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation of knot size), checks and splits. Some voids are allowed.

Face lamella:

4 mm sawn hardwood

Core layer:

13 mm SPF finger core, predominantly Qtr. Sawn

Back layer:

2 mm wood veneer

Sanding:

Can be professionally sanded 3-4 times

Radiant Heat:

Approved over Radiant heat

Installation Method:

Glue down

Subfloor:


Plywood or concrete



Relative Humidity Chart



Installation methods



Consult Vintage's Radiant Heat compliance information at vintageflooring.com

PATTERNS




CHEVRON



SPEARHEAD



BROOKLYN BRIDGE



LEAF LINE



BOARDWALK



Brushed White Oak Character Atlantis UVF

LIFETIME
stability warranty

LIFETIME
structural warranty

35 YEARS
residential wear warranty

3 YEARS
commercial wear warranty