



UV URETHANE OIL FINISH COLLECTION

SMOOTH	WIRE BRUSHED				ETCHED
WHITE OAK	RED OAK	ASH	WHITE OAK	WHITE OAK	MAPLE
NATURAL*	NATURAL*	GLASGOW	ORION*	ZEUS*	ICELAND
ATHENA*	TITAN*	KALAHARI	ATLANTIS*	GOTHAM*	MALDIVES
APOLLO*	KAHLUA*	MANCHESTER	PHARAOH*	BAROQUE*	SAMOA
NAUTILUS*	CHARIOT*	COBBLESTONE		BUCKINGHAM*	BORNEO
EXCALIBUR	BERKSHIRE*	COVENTRY		WHITE OAK RIFT & QTR SAWN	GALAPAGOS
GABON*	GRYPHON*	BOARDWALK		NATURAL	TAHITI
OLD OAK	PEWTER*			NAUTILUS	
BLACK OAK	COCOA*			GOTHAM	BLACK WALNUT
		HAND SCRAPED WHITE OAK		BUCKINGHAM	NATURAL
		NATURAL	OLD OAK	BUCKINGHAM	
		NAUTILUS	BUCKINGHAM	BUCKINGHAM	
		GOTHAM	BAROQUE	BAROQUE	

*Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.

UV URETHANE OIL FINISH SPECIFICATIONS

Product Type:	3/4 (19mm) Solid Sawn® Structured* 3/4" (19mm) Northern Solid Sawn™ Structured* 3/4" (19 mm) Pioneered® Solid* 3/4" (19mm) Northern Solid Sawn™ Structured Herringbone
Product Species:	Ash, Red Oak, White Oak, Maple, Black Walnut*
Product Width:	Ash : 2 1/4", 3 1/4", 4 1/4"* Red Oak : 3 1/4", 5"* White Oak : 3 1/4", 5", 7"* Maple : 3 1/4", 4 1/4", 4 3/8", 5"* Black Walnut : 4 3/8", 5"* Herringbone: Estate or Select-V 3 1/4" x 14.68", Character 5" x 30". See Herringbone specification sheet for details
Product Gloss:	UV Urethane Oil
Product Grade:	Select-V – Color variation and naturally occurring characteristics Heritage – Color variation with unlimited knots Character – Naturally occurring characteristics, sound knots and checking
Product Construction:	Microbevel on 4 sides
Installation Method:	Nail (Pioneered®) Nail, Glue, Float (Solid Sawn®, Northern Solid Sawn™ Structured) Herringbone: Glue
Radiant Heat:	Maple, Red Oak, White Oak and Black Walnut Northern Solid Sawn™, Solid Sawn®
Structural Warranty:	Lifetime
Lifetime Stability Warranty:	Solid Sawn® Relative humidity must be maintained between 25% – 70% Northern Solid Sawn™ Relative humidity must be maintained between 25-70% Pioneered® Relative Humidity must be maintained between 40 – 50%
Residential Warranty:	10-year – UV Urethane Oil
Commercial Warranty:	1-Year Limited Warranty – UV Urethane Oil



*Not all species are warranted over radiant heat. Consult your dealer for further information.



* Refer to availability chart for details.

