

SMOOTH COLLECTION

SMOOTH						
MAPLE		RED OAK		HICKORY	WHITE OAK	
NATURAL	REMBRANDT	NATURAL*	GALLIANO	NATURAL	NATURAL*	OLD OAK
OXFORD	GODIVA	CHABLIS	CAMBRIDGE	CHIVAS	NAUTILUS	BUCKINGHAM
PEGASUS	TABOO PEARL	BRANDY	KAHLUA*	NILE	ORACLE	BAROQUE
WINDSOR	SLATE	BOURBON	CHARIOT*	THAMES	ATHENA*	GOTHAM
ARIES	VIENNA	мосна*	COCOA*	OLD MISSION	APOLLO*	BLACK OAK
NEBULA	MOROCCO	BERKSHIRE*	PEWTER*	WINCHESTER	GABON	EXCALIBUR
BLACK WALNUT NATURAL MEDIEVAL		GRYPHON*		MOOREA		GREYSTOKE
				MESQUITE		

^{*} Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.



Product Type: 3/4" (19 mm) Solid Pioneered®

9/16" (13.7 mm) Engineered Crafted®

3/4" (19mm) Structured Northern Solid Sawn®

3/4 (19mm) Structured Solid Sawn®

7/16" (11 mm) Click*U-Loc®

Product Species: Maple, Red Oak, Hickory, White Oak, Black Walnut

Product Grades &

Select-V, Estate, Character, Heritage*

Width:

Herringbone: Red Oak Estate 3 1/4" (84 mm) x 14.68" (372 mm)

White Oak Select-V: 3 1/4" (84 mm) x 14.68" (372 mm)

Character 5" (127 mm) x 30" (762 mm)

Product Lengths: Depends on products, species and grades, refer to species and grade sell sheet.

Gloss: Depends on products, species and grade *

Installation Method: Refer to product specifications sell sheets

Radiant Heat: Maple, Red Oak, White Oak and Black Walnut - Crafted®, Northern Solid Sawn®,

Solid Sawn®, U-Loc®, see radiant heat warranty.

Structural Warranty: Lifetime

Lifetime Stability Warranty:

Residential Warranty:

Pioneered® Relative Humidity must be maintained between 40 – 50%

Crafted® Relative humidity must be maintained between 40% - 60%

Northern Solid Sawn® Relative humidity must be maintained between 25-70% Solid Sawn® Relative humidity must be maintained between 25% – 70% U-Loc® Relative humidity must be maintained between 40% – 60%

25-year Wear Warranty – Pearl and Semi-gloss

10-year - UV Urethane Oil

Commercial Warranty: 3–Year Limited Warranty – Pearl and Semi-gloss

1-Year Limited Warranty - UV Urethane Oil





^{*} Refer to availability chart for details.