

SMOOTH COLLECTION



White Oak Smooth, Nautilus

SMOOTH											
MAPLE		RED OAK		HICKORY		WHITE OAK					
NATURAL	BERKLEY	NATURAL*	GALLIANO	NATURAL	NATURAL*	OLD OAK					
SAHARA	REMBRANDT	CHABLIS	CAMBRIDGE	CHIVAS	NAUTILUS	BUCKINGHAM*					
OXFORD	GODIVA	BOURBON	KAHLUA*	NILE	ORACLE*	BAROQUE*					
PEGASUS	TABOO PEARL	MOCHA*	CHARIOT*	THAMES	ATHENA*	GOTHAM*					
WINDSOR	SLATE	BERKSHIRE*	COCOA*	OLD MISSION	APOLLO*	BLACK OAK					
NEBULA	MOROCCO	GRYPHON*	PEWTER*	WINCHESTER	GABON	EXCALIBUR					
		BAJA*	DOVER*	MOOREA							
				MESQUITE							
				GOBI							
BLACK WALNUT											
NATURAL	MEDIEVAL										

* Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.



SMOOTH SPECIFICATIONS

Product Type:	3/4" (19 mm) Pioneered® Solid 3/4" (19mm) Northern Solid Sawn® Structured 3/4 (19mm) Solid Sawn® Structured
Product Species:	Maple, Red Oak, Hickory, White Oak, Black Walnut
Product Grades & Width:	Maple - Pioneered® Estate and Select-V 2 1/4" , 3 1/4", 4 1/4" Northern Solid Sawn® Estate and Select-V 3 1/4", 4 3/8", 5" Red Oak - Pioneered® Estate and Select-V 2 1/4" , 3 1/4", 4 1/4" Northern Solid Sawn® Estate 3 1/4", 4 3/8" Northern Solid Sawn® Character 6 1/2" Northern Solid Sawn® Herringbone 3 1/4" x 14.68" Hickory - Pioneered® Select-V 2 1/4" , 3 1/4", 4" Solid Sawn® Select-V 3 1/4", 4" Solid Sawn® Character 5", 7" White Oak - Northern Solid Sawn® Select-V 3 1/4", 4 3/8" Northern Solid Sawn® Character 5", 6 1/2" Solid Sawn® Character 5", 7", 8" Solid Sawn® Rift & Qtr. Sawn Select-V 5" Northern Solid Sawn® Herringbone 3 1/4" x 14.68", 5" x 30" Walnut: Northern Solid Sawn® Select-V 4 3/8", 5" Northern Solid Sawn® Character 4 3/8", 5"
Product Lengths:	Depends on products, species and grades, refer to species and grade sell sheet.
Gloss:	Depends on products, species and grade *
Installation Method:	Refer to product specifications sell sheets
Radiant Heat:	Maple, Red Oak, White Oak and Black Walnut - Northern Solid Sawn®, Solid Sawn®, U-LOC®, see radiant heat warranty.
Structural Warranty:	Lifetime
Lifetime Stability Warranty:	Pioneered® Relative Humidity must be maintained between 40 – 50% Northern Solid Sawn® Relative humidity must be maintained between 25-70% Solid Sawn® Relative humidity must be maintained between 25% – 70% U-LOC® Relative humidity must be maintained between 40% – 60%
Residential Warranty:	25-year Wear Warranty – Pearl and Semi-gloss 10-year – UV Urethane Oil
Commercial Warranty:	3-Year Limited Warranty – Pearl and Semi-gloss 1-Year Limited Warranty – UV Urethane Oil

* Refer to availability chart for details.

