

PIONEERED® SOLID SPECIFICATIONS

Product Type:

3/4" (19mm) solid Tongue and groove with micro-v bevel on 4 sides

Product Species:

Product Textures & Gloss:

Hickory, Maple, Oak, Red Oak

Smooth: Hickory, Maple, Red Oak Pearl Wire Brushed: Red Oak UVF

Sculpted: UVF Blade: UVF

Product Lengths:

Select-V: 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm) **Character:** 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm)

Product Grade & Width:

Sanding:

Radiant Heat:

Installation Method:

Hickory: Character 2 1/4", 3 1/4", 4 1/4" Maple: Select-V 2 1/4", 3 1/4", 4 1/4"

Oak: Character 4 1/4"

Red Oak: Select-V 2 1/4", 3 1/4", 4 1/4"

Character 4 1/4"

Select-V: Color variation and naturally occuring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade.

Character: Unlimited color variation and naturally occuring charactertistics, sound filled knots (no limitation of knot size) checks and splits. Some voids are allowed.

Can be professionally sanded 3-4 times

Not approved over Radiant heat

Plank: Nail down on plywood at or above ground level

Subfloor: Plywood



IONLEINED SOLID SI ECII ICATIOI

PIONEERED*

3/4*
19mm
Thickness

Relative Humidity Chart



Installation methods





LIFETIME stability warranty LIFETIME structural warranty 35 YEARS residential wear warranty

3 YEARS commercial wear warranty

23/

