

# SCULPTED SPECIFICATIONS

## Product Type:

3/4" (19mm) Solid  
3/4" (19mm) Northern Solid Sawn® Structured  
3/4" (19mm) Northern Solid Sawn® Structured Herringbone  
Tongue and groove

## Product Species:

Black Walnut, Hickory, Maple, Oak, White Oak

## Product Gloss:

UVF

## Product Lengths:

**Solid Character: 4 1/4"**  
10" - 76" Average 32" (254 mm - 1930 mm Ave 813 mm)  
**Northern Solid Sawn® Character: 5", 6 1/2", 7 3/4"**  
20" - 82" Average 42" (511 mm - 2086 mm Ave 1067 mm)

## Product Grade & Width:

**Black Walnut:** Northern Solid Sawn® Character 5", 6 1/2"  
**Hickory:** Northern Solid Sawn® Character 5", 6 1/2"  
**Maple:** Northern Solid Sawn® Character 5", 6 1/2"  
**Oak:** Solid Character 4 1/4"  
Northern Solid Sawn® Character 5", 6 1/2", 7 3/4"  
**White Oak:** Northern Solid Sawn® Character 5", 6 1/2", 7 3/4"  
Herringbone Character 5" x 30"

**Character:** Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation of knot size), checks and splits. Some voids are allowed.

## Sanding:

Can be professionally sanded 3-4 times

## Radiant Heat:

**Solid:** Not approved over Radiant heat  
**Northern Solid Sawn®:** All species are approved over Radiant heat except Hickory

## Installation Method:

**Solid:** Nail down on plywood at or above ground level  
**Northern Solid Sawn® Plank:** Nail, glue or float at, above or below grade  
**Herringbone:** Glue

## Subfloor:

**Solid:** Plywood  
**Northern Solid Sawn®:** Plywood or concrete



Black Walnut Character Natural UVF



### Relative Humidity Chart



### Installation methods



### Relative Humidity Chart



### Installation methods



Floated installation relative humidity warranty is 30 - 60%

Consult Vintage's Radiant Heat compliance information at [vintageflooring.com](http://vintageflooring.com)

**LIFETIME**  
stability warranty

**LIFETIME**  
structural warranty

**35 YEARS**  
residential wear warranty

**3 YEARS**  
commercial wear warranty