

## HAND SCRAPED

Hand Scraped hardwood has a distinct look and old world feel that goes back hundreds of years. Each board of Vintage Hand scraped hardwood flooring is unique, scraped and crafted by hand then stamped on the back by the craftsman. Hand scraped floors tend to require less maintenance than smooth finish floors and help hide everyday wear. They are contoured to accentuate the natural beauty and character of each species.

## White Oak, Gotham

MAPLE WHITE OAK **HICKORY** GOTHAM\* NATURAL WINCHESTER NATURAL\* NATURAL OXFORD **BUCKINGHAM\*** CHIVAS MOOREA PEGASUS WINDSOR ORACLE\* THAMES MESQUITE MOROCCO NAUTILUS\* OLD OAK OLD MISSION NEBULA NILE GODIVA OTHELLO\* BAROQUE\* GREYSTOKE REMBRANDT TABOO **BLACK WALNUT** NATURAL MEDIEVAL

\* Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.



## HAND SCRAPED SPECIFICATIONS

		SOLID SAWN <sup>®</sup>
Product Type:	Structured Solid Sawn <sup>®</sup> - Authentic Hand Scraped	4 mm Sawn wear lamella Solid finger lumber core
Product Species:	Black Walnut, Hickory, Maple, White Oak	Hardwood back Superior lengths : 16"- 87"
Product Grades & Width: Availability of widths will vary by grade and color.	Black Walnut Character: 5" (127mm), 7" (177mm) Hickory Character: 5" (127mm), 7" (177mm) Maple Character: 5" (127mm) White Oak Character: 3 1/4" (83mm), 5" (127mm),	(406 mm - 2210 mm)
Refer to availability chart for more information.	7" (177 mm), 10" (254 mm) Herringbone White Oak Character: 5" (127 mm) x 30" (762 mm)	$\sim$
Product Lengths:	Character: 16"– 87" Average 48" (406 mm-2209 mm Ave. 1219 mm) Character: 10" White Oak 24" – 115" Average 58" (254 mm 609 mm-2921 mm Ave. 1219 mm)	YES - ABOVE GROUND LEVEL YES - GROUND LEVEL YES - BELOW GROUND LEVEL
Product Gloss:	Pearl (low gloss), UV Oil, and Semi gloss by special order	YES ¬ RADIANT HEAT
Product Grade:	Character with filled voids	Consult Vintage's radiant heat compliance
Product Construction:	3/4" (19mm) 3 ply, Solid Sawn	information available at www.vintageflooring.com
Face Lamella:	4mm Solid Species	Relative Humidity Chart
Core Layer:	10mm Solid Finger construction of same species or alike species	
Back Layer	5mm Solid Sawn construction of same species or alike species	<b>25-70%</b> 3/4" (19 mm) Structured
Installation Method:	Nail, Glue or Float Herringbone Glue	
Radiant Heat:	Contact a Vintage dealer for approved species over radiant heat	NAIL GLUE FLOAT
Structural Warranty:	Lifetime Structural Warranty	
Lifetime Stability Warranty:	Relative humidity must be maintained between 25% – 70%	
Residential Warranty:	25-Year Wear Warranty for Pearl and Semi-gloss 10-Year Wear Warranty for UV Urethane Oil	
Commercial Warranty:	3-Year Wear Warranty for Pearl and Semi-gloss 1-Year Wear Warranty for UV Urethane Oil	



