

Vintage's Canadian made Northern Solid Sawn® is the next generation of high performing structured hardwood floors. Backed by the best stability warranty in the business and trend hitting colors, textures and widths will provide you with a lifetime of satisfaction.



Maple, Pegasus

SMOOTH				WIRE BRUSHED			ETCHED
MAPLE		RED OAK	WHITE OAK	RED OAK		WHITE OAK	MAPLE
NATURAL	NEBULA	NATURAL*	NATURAL*	NATURAL*	GRYPHON*	ATLANTIS*	ICELAND
OXFORD	MOROCCO	KAHLUA*	NAUTILUS*	KAHLUA*	PEWTER*	PHARAOH*	MALDIVES
PEGASUS	REMBRANDT	MOCHA*	ORACLE*	BERKSHIRE*	VENUS*	ORION*	SAMOA
WINDSOR	GODIVA	BERKSHIRE*	ATHENA*	CHARIOT*	MOJAVE*	ZEUS*	BORNEO
ARIES	TABOO	CHARIOT*	APOLLO*	COCOA*	ZAMBEZI*	GOTHAM*	GALAPAGOS
BLACK WALNUT		COCOA*	GABON*	TITAN*		BAROQUE*	TAHITI
		GRYPHON*	BUCKINGHAM*			BUCKINGHAM*	BLACK WALNUT
NATURAL	MEDIEVAL	PEWTER*	BAROQUE*				NATURAL
			GOTHAM*				

* Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.

NORTHERN SOLID SAWN[®] SPECIFICATIONS



Product Type:

Structured Northern Solid Sawn[®]

Product Species:

Black walnut, Maple, Red Oak, White Oak

Product Grade & Width:

Availability of widths will vary by grade and color. Refer to availability chart for more information.

Select-V : 3-1/4" (84 mm), 4-3/8" (112 mm), 5" (127 mm)
Character : 5" (127 mm)

Herringbone Red Oak Estate : 3-1/4" (84 mm) x 14.68 (372 mm)

White Oak Select-V : 3-1/4" (84 mm) x 14.68 (372 mm)

Character : 5" (127 mm) x 30" (762 mm)

Product Lengths:

Estate & Select-V: 15" - 70" Average 33" (381 mm - 1750 mm Ave. 838 mm)

Character: 20" - 83" Average 42" (511 mm - 2108 mm Ave. 1066 mm)

Product Gloss:

White Oak Select-V: Pearl

Red Oak Estate: Semi-gloss & Pearl

Black Walnut, Maple Estate & Select-V: Pearl

Maple, White Oak Character: Pearl

Wire Brushed Red Oak, White Oak Character: UV Urethane Oil

Etched Maple Estate & Walnut Select-V: UV Urethane Oil

Product Grade:

Estate – Best grade available

Select-V: Color variation and naturally occurring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade.

Character: Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation in knot size) checks and splits. Some voids are allowed.

Product Thickness:

3/4" (19 mm) 3 ply structured

Face Lamella:

4mm

Core Layer:

13 mm SPF Qtr. Sawn

Back Layer

2 mm Hardwood veneer

Installation Method:

Nail, Glue or Float

Sanding

Herringbone: Glue

Can be professionally sanded 3-4 times

Radiant Heat:

Yes for all species, see Radiant Heat Warranty

Structural Warranty:

Lifetime

Lifetime Stability Warranty:


Relative humidity must be maintained between 25-70%

Residential Warranty:

25-Year for Pearl & Semi-gloss, 10-Year for UV Urethane Oil


Commercial Warranty:

3-Year for Pearl & Semi-gloss, 1-Year for UV Urethane Oil



Consult Vintage's radiant heat compliance information available at www.vintageflooring.com

Relative Humidity Chart



3/4" (19 mm) Structured

