




Our line of Pioneered® Solid Hardwood floors comes in a wide selection of colors, species and widths. Including 2 beautiful textures, Wire Brushed on Ash and Red Oak, and Vintage's proprietary Etched available on Maple. Our longer average lengths make for easy installation and a more elegant look.



SMOOTH					WIRE BRUSHED		ETCHED
HICKORY	MAPLE		RED OAK		RED OAK	ASH	MAPLE
NATURAL	NATURAL	PEGASUS	NATURAL —	GALLIANO	NATURAL	GLASGOW	ICELAND
CHIVAS	OXFORD	ARIES	CHABLIS	CAMBRIDGE	KAHLUA	KALAHARI	MALDIVES
NILE	VIENNA	NEBULA	BRANDY	KAHLUA	CHARIOT	MANCHESTER	SAMOA
THAMES	WINDSOR	REMBRANDT	BOURBON	CHARIOT	BERKSHIRE	COBBLESTONE	BORNEO
OLD MISSION	MOROCCO	SLATE	МОСНА	COCOA	COCOA	BOARDWALK	GALAPAGOS
WINCHESTER	GODIVA		BERKSHIRE	PEWTER	TITAN	COVENTRY	TAHITI
MOOREA	TABOO PEARL		GRYPHON		GRYPHON		
MESQUITE					PEWTER		

PIONEERED® SPECIFICATIONS

Product Type: 3/4" (19 mm) Pioneered® Solid Hardwood

Product Species: Ash, Maple, Hickory, Red Oak

Product Width: Ash: 21/4", 31/4", 41/4"

Maple: 21/4", 31/4", 41/4 Hickory: 21/4", 31/4", 41/4 Red Oak: 21/4", 31/4", 41/4"

Product Lengths: Estate: 12" - 79" Average 38"*

Select-V: 12" - 79" Average 32"* Heritage: 10" - 79" Average 30"*

* Lengths and average length may vary by width.

Product Gloss: Smooth: Semi gloss or Pearl available. Pearl will become

the standard in 2017. UV Oil available by special order. UV urethane oil is standard on Etched & Wire Brushed.

Product Grade: Estate – Best grade available

Select-V - Color variation and naturally occurring

characteristics

Heritage - Color variation with unlimited knots

Product Construction: Microbevel on 4 sides

Installation Method: Install only on plywood that is on ground level or above,

Nail down

Structural Warranty: Lifetime

Lifetime Stability Relative Humidity must be maintained between

40 - 50%


Residential Warranty: 25-year Wear Warranty – Pearl and Semi-gloss

10-year - UV Urethane Oil

Commercial Warranty: 3-Year Limited Warranty - Pearl and Semi-gloss


1-Year Limited Warranty - UV Urethane Oil







- Made from 100% solid hardwood, dried to 6-9% moisture content.
- Install over a 5/8" plywood, 5/8" T-G wood or 23/32" OSB subfloor





Warranty:





