

Vintage's Wire Brushed floors are another unique and beautiful option for a textured floor. The brushing technique with its UV Urethane Oil finish is a perfect mix, as the UV Oil enhances the wood, preserving the natural look and feel of the brushing. These floors tend to hide dents and scratches extremely well and everyday wear is blended in. Wire brushing is very conducive to achieving 2 tone floors, giving you a European style and look.

White Oak, Atlantis

RED OAK		ASH		WHITE OAK		WHITE OAK RIFT & QTR SAWN	
NATURAL*	TITAN	GLASGOW	ORION*	ZEUS*	NATURAL		
KAHLUA*	GRYPHON*	KALAHARI	ATLANTIS*	GOTHAM*	NAUTILUS		
CHARIOT*	PEWTER*	MANCHESTER	PHARAOH*	BUCKINGHAM*	GOTHAM		
BERKSHIRE*	COCOA*	COBBLESTONE		BAROQUE*	BUCKINGHAM		
MOJAVE*	VENUS*	COVENTRY		SPARTACUS	BAROQUE		
DOVER*	ZAMBEZI*	BOARDWALK					

* Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.

WIRE BRUSHED SPECIFICATIONS

Product Type:

- 3/4" (19mm) Pioneered® Solid
 - 3/4" (19mm) Northern Solid Sawn® Structured
 - 3/4" (19mm) Solid Sawn® Structured
 - 3/4" (19mm) Northern Solid Sawn® Herringbone Structured
 - 3/4" (19mm) U-LOC® Locking
- *Refer to availability chart for details

Product Species & colors:

- Ash: Boardwalk, Cobblestone, Coventry, Glasgow, Kalahari, Manchester
- Red Oak: Natural, Kahlua, Chariot, Berkshire, Cocoa, Dover, Gryphon, Pewter, Titan, Mojave, Venus, Zambezi
- White Oak: Atlantis, Baroque, Buckingham, Gotham, Orion, Pharaoh, Zeus, Spartacus
- Rift & Qtr. Sawn White Oak: Natural, Baroque, Buckingham, Gotham, Nautilus

Product Grade & Width:

- Ash - Pioneered® Select-V 2 1/4", 3 1/4", 4 1/4"
- Red Oak - Pioneered® Select-V 3 1/4"
- Pioneered® Heritage 3 1/4"
- Northern Solid Sawn® Select-V 3 1/4"
- Northern Solid Sawn® Character 5", 6 1/2"
- Northern Solid Sawn® Herringbone 3 1/4"x14.68", 5"x30"
- U-LOC® Select-V 4 1/4"
- White Oak - Northern Solid Sawn® Select-V 3 1/4"
- Northern Solid Sawn® Character 5", 6 1/2"
- Solid Sawn® Character 7", 8"*
- Solid Sawn® Rift & Qtr. Sawn Select-V 5", 7"
- Northern Solid Sawn® Herringbone
- U-LOC® Select-V 4 1/4"

Product Lengths:

- Pioneered® Solid Select-V: 12"-79" average 32"
- Pioneered® Solid Heritage: 10"-84" average 30"
- Northern Solid Sawn® Structured: Select-V 15" - 70" average 37"
- Northern Solid Sawn® Structured: Character 20"-83" average 42"
- Solid Sawn® Structured: Rift&Qtr. Select-V 14"-78" average 38"
- Solid Sawn® Structured: 7" Character 18" - 84" average 44"
- Solid Sawn® Structured: 8" Character 24" - 115" average 58"
- U-LOC® Select-V: 13.77"-46.14"

Product Gloss:

UV Urethane Oil

Product Construction:

Tongue & Groove, microbevel on 4 sides

Installation Method:

- Pioneered® Solid - Nail
- Northern Solid Sawn® & Solid Sawn® - Nail, Glue or Float
- Herringbone Northern Solid Sawn® - Glue
- U-LOC® - Float

Structural Warranty:

Lifetime

Lifetime Stability Warranty:

Relative humidity must be maintained between 40% - 50% for Pioneered® Solid
25% - 70% for Northern Solid Sawn® and Solid Sawn®

Residential Warranty:

10-Year Wear Warranty

Commercial Warranty:



1-Year Wear Warranty

Care & Maintenance:



See Vintage UV Oil Care & Maintenance instructions



Relative Humidity Chart



Relative Humidity Chart



Relative Humidity Chart

