



A modern twist on traditional Hand Scraped hardwood floors, made in Canada from premium Oak hardwood. "Sculpting" the wood adds depth, detail, and practicality for daily use. Another great choice to help hide everyday wear.



HICKORY MAPLE RED OAK WHITE OAK SENTINEL NOVA OASIS* **RIDGELINE*** ATHENA* ANGORA* APOLLO* **GOBI** SAHARA **DOVER*** NATURAL NATURAL **BARISTA*** HARBOR* **NAUTILUS*** CHIVAS **PEGASUS** SAND DUNE* CANVAS* PEWTER* NEBULA NATURAL* OLYMPUS HIGHLAND* NATURAL* BAUHAUS* **BERKLEY** NILE **OLD MISSION** REMBRANDT OPHELIA* **BUCKINGHAM*** WINCHESTER GOTHAM* MOOREA **MESQUITE BAROQUE*** *These species and colors are available in Herringbone. Refer to the Herringbone

specification sheet for more information.

SCULPTED SPECIFICATIONS

Product Type: 3/4" (19 mm) Pioneered ® Solid

3/4" (19mm) Northern Solid Sawn® Structured

Product Texture: Sculpted

Colors

Width:

Hickory: Natural, Chivas, Gobi, Olympus, Nile, Old Mission, **Product Species &**

Winchester, Moorea, Mesquite, Sentinel Maple: Sahara, Berkley, Pegasus, Nebula,

Rembrandt, Nova, Natural

Red Oak: Harbor, Highland, Hillside, Pewter, Ridgeline, Sand Dune, Dover, Natural, Angora, Oasis, Ophelia, Barista

White Oak: Athena, Apollo, Bauhaus, Buckingham, Baroque, Nautilus, Gotham, Natural, Canvas

Walnut: Natural, Heirloom

Hickory, Maple and Black Walnut: **Product Grades &**

Northern Solid Sawn® Character 5", 6 1/2"

Red Oak: Pioneered® Character 4 1/4"

Northern Solid Sawn® Character 5", 6 1/2", 7 3/4"

and Herringbone 5" x 30"

White Oak: Northern Solid Sawn® Character 5", 6 1/2", 7 3/4"

and Herringbone 5" x 30"

Product Lengths: Northern Solid Sawn®: 20" - 82" Average 42"

(511 mm- 2086 mm Average 1067 mm)

Pioneered® Solid: 12" - 79" (305 mm - 2007 mm) Herringbone NSS®: 5" - 30" (127 mm - 762 mm)

Product Gloss: UVF

Product Construction: Bevelled Edge

Pioneered®: Nail Installation Method:

Northern Solid Sawn®: Nail, Glue or Float

Pioneered®: Not Approved on Radiant Heat. **Radiant Heat:**

Northern Solid Sawn®: All species except Hickory are

approved on Radiant Heat.

Lifetime Structural Warranty:

Pioneered®: Relative humidity must be maintained between Lifetime Stability

Warranty:

Northern Solid Sawn®: Relative humidity for nail or glued down installation must be maintained between 25 - 80%

and for floated installation between 30 - 60%

Residential Warranty: 35-Year Wear Warranty for UVF


Commercial Warranty: 3-Year Wear Warranty for UVF



















Consult Vintage's radiant heat compliance information available at www.vintageflooring.com











^{*} Refer to availability chart for details.