

# WIRE BRUSHED SPECIFICATIONS

**Product Type:**

3/4" (19mm) Pioneered® solid  
 3/4" (19mm) Northern Solid Sawn® Structured  
 3/4" (19mm) Northern Solid Sawn® Structured Chevron  
 3/4" (19mm) Northern Solid Sawn® Structured Herringbone  
 3/4" (19mm) Solid Sawn® Structured  
 Tongue and groove with bevel on 4 sides

**Product Species:**

Black Walnut, Red Oak, White Oak plain sawn & Rift & Qtr. Sawn

**Product Gloss:**

UVF

**Product Lengths:**

**Pioneered® solid Select-V:** 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm)  
**Pioneered® solid Character:** 12" - 79" Average 32" (305 mm - 2007 mm Ave 813 mm)  
**Northern Solid Sawn® Select-V:** 3 1/4", 4 3/8" 15" - 70" Average 33" (373 mm - 1778 mm Ave 838 mm)  
**Northern Solid Sawn® Select-V Rift & Qtr. Sawn** 5", 6 1/2" 20" - 82" Average 42" (511 mm - 2086 mm Ave 1067 mm)  
**Northern Solid Sawn® Character:** 5", 6 1/2", 7 3/4" 20" - 82" Average 42" (511 mm - 2086 mm Ave 1067 mm)  
**Northern Solid Sawn® Chevron: Character** 24.4" (620 mm)  
**Herringbone: Select-V** 14.68" (373mm), **Character** 30" (762mm)

**Product Grade & Width:**

**Red Oak: Pioneered® solid Select-V** 3 1/4", **Character** 4 1/4"  
**Northern Solid Sawn® Select-V** 3 1/4", **Character** 5", 6 1/2", 7 3/4"  
**White Oak: Northern Solid Sawn® Plain Sawn Select-V** 3 1/4", **Rift & Qtr. Sawn** 5", 6 1/2"  
**Character** 5", 6 1/2", 7 3/4"  
**Chevron Character:** 5" x 24.4"  
**Herringbone Select-V** 3 1/4", 14.68", **Character** 5" x 30"  
**Solid Sawn® Character** 7", 8"

**Select-V:** Color variation and naturally occurring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade.

**Character:** Unlimited color variation and naturally occurring characteristics, sound filled knots (no limitation of knot size), checks and splits. Some voids are allowed.

**Sanding:**

Can be professionally sanded 3-4 times

**Radiant Heat:**

**Pioneered®:** Not approved over Radiant heat  
**Northern Solid Sawn®:** Approved over Radiant heat

**Installation Method:**

**Pioneered® solid:** Nail down on plywood at or above ground level  
**Northern Solid Sawn® Plank:** Nail, glue or float at, above or below grade  
**Chevron & Herringbone:** Glue

**Subfloor:**

Plywood



Relative Humidity Chart



Installation methods



**LIFETIME**  
stability warranty

**LIFETIME**  
structural warranty



Relative Humidity Chart



Installation methods



Floated installation relative humidity warranty is 30 - 60%

Consult Vintage's Radiant Heat compliance information at [vintageflooring.com](http://vintageflooring.com)

**35 YEARS**  
residential wear warranty

**3 YEARS**  
commercial wear warranty