



Vintage's Canadian made Northern Solid Sawn[™] is the next generation of high performing structured hardwood floors. Backed by the best stability warranty in the business and trend hitting colors, textures and widths will provide you with a lifetime of satisfaction.

Maple, Pegasus

SMOOTH					WIRE BRUSHED		ETCHED
MAPLE		RED OAK	WHITE OAK	BLACK WALNUT	RED OAK	WHITE OAK	MAPLE
NATURAL	NEBULA	NATURAL*	NATURAL*	NATURAL	NATURAL*	ATLANTIS*	ICELAND
OXFORD	MOROCCO	KAHLUA*	NAUTILUS*	MEDIEVAL	KAHLUA*	PHARAOH*	MALDIVES
PEGASUS	REMBRANDT	MOCHA*	ORACLE*		BERKSHIRE*	ORION*	SAMOA
WINDSOR	GODIVA	BERKSHIRE*	ATHENA*		CHARIOT*	ZEUS*	BORNEO
ARIES	ТАВОО	CHARIOT*	APOLLO*		COCOA*	GOTHAM*	GALAPAGOS
		COCOA*	GABON*		TITAN*	BAROQUE*	ТАНІТІ
		GRYPHON*	BUCKINGHAM*		GRYPHON*	BUCKINGHAM*	BLACK WALNUT
		PEWTER*	BAROQUE*		PEWTER*		15 L
available in Herrin	se species and colors gbone. Refer to the t for more informatio	Herringbone	GOTHAM*				



NORTHERN SOLID SAWN[™] SPECIFICATIONS

Product Type:	Structured Northern Solid Sawn™	
Product Species:	Black walnut, Maple, Red Oak, White Oak	• 4 mm Sawn Wear layer
Product Grade & Widths: Availability of widths will vary by grade and color. Refer to availabil- ity chart for more information.	Select-V: 3 1/4"(84mm), 4 3/8"(112 mm), 5"(127mm) Character: 5"(127 mm) Herringbone: Red Oak Estate 3 1/4"(84 mm) x 14.68" (372 mm) White Oak Select-V: 3 1/4"(84 mm) x 14.68" (372 mm), Character 5"(127 mm) x 30"(762 mm)	Small micro-v bevel S
Product Lengths:	Estate & Select-V: 15" - 70" Average 33" (381 mm - 1750 mm Ave. 838 mm) Character: 20" - 83" Average 42" (511 mm - 2108 mm Ave. 1066 mm)	
Product Gloss:	White Oak Select-V: Pearl Red Oak Estate: Semi-gloss & Pearl Black Walnut, Maple Estate & Select-V: Pearl Maple, White Oak Character: Pearl Wire Brushed Red Oak, White Oak Character: UV Urethane Oil Etched Maple Estate & Walnut Select-V: UV Urethane Oil	ABOVE GROUND LEVEL
Product Grade:	Estate – Best grade available Select-V: Color variation and naturally occuring characteristics, 1/4" sound filled knots, some voids are allowed. Splits, checks and knots on bevel are not part of this grade. Character: Unlimited color variation and naturally occuring character- istics, sound filled knots (no limitation in knot size) checks and splits. Some voids are allowed.	rst RADIANT HEAT
Product Thickness:	3/4" (19 mm) 3 ply structured	Nail
Face Lamella:	4mm	Glue
Core Layer:	13 mm SPF Qtr. Sawn	Side
Back Layer	2 mm Hardwood veneer	Float
Installation Method: Sanding:	Nail, Glue or Float Herringbone: Glue Can be professionally sanded 3-4 times	
Radiant Heat:	Yes for all species, see Radiant Heat Warranty	40% 50% 60% 70%
Structural Warranty:	Lifetime	25% 30% 70% 80%
Lifetime Stability Warranty:	Relative humidity must be maintained between 25-70%	90%
Residential Warranty:	25-Year for Pearl & Semi-gloss, 10-Year for UV Urethane Oil	3/4" (19 mm) Northern Solid Sawn™ 25-70%
Commercial Warranty:	3-Year for Pearl & Semi-gloss, 1-Year for UV Urethane Oil	





409 Evans Ave. Toronto, Ontario M8Z 1K8 Tel: (416) 252-0962 Toll Free: 1-877-256-0231 16/03